

# roman blind two point measure

step one print this page and follow the instructions

## The advantages of an outside fit are:

- The blind will fold up fully or partly above the window and will not affect light levels so much.
- You determine the exact size of the blind and where it is fitted

## The disadvantages of an outside fit are:

- They can collect dust along the top of the battons.
- They need to be secured to nogs and studs.



**1** When measuring, always look out for things like window handles, or anything that could obstruct the blinds easy operation. This will ensure of a perfect fit.

**2** Always measure width first then length.

**3** Measure the frame from left to right. Again, double check it. (mm)\_\_\_\_\_

**4** Add to this measurement the distance you want the blind to extend beyond each side of the frame. (If 50mm each side add 100mm) (mm)\_\_\_\_\_ This is the final width of the blind. *(final width measurement)*

**5** Take the measurement from the top to the bottom of the window frame. Double check it - this is crucial. (mm)\_\_\_\_\_

**6** An open Roman blind (pulled up) has a stack of 250mm–300mm depending on the actual full length of the blind, take this into account when measuring. You may want to hang the blind higher to minimise window coverage when open.

**7** Add to this measurement the distance you want the blind to extend beyond the top and bottom of the frame (If 200mm above and 100mm below, add 300mm.) (mm)\_\_\_\_\_ This is the final length of the blind. *(final length measurement)*